

Laundromat **Stacked & Single Tumble Dryer** Specifications

Models		HTT30	HTT55	HT075	HT120
Control Options		Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch/600	Galaxy™ Touch
Capacity – lb (kg)		30 (13) x 2	55 (25) x 2	75 (34)	120 (55)
Width – in (mm)		31.5 (800)	34.4 (874)	38.5 (978)	46.4 (1179)
Depth – in (mm)	Standard	43.6 (1107)	54.4 (1382)	53.0 (1346)	67.9 (1725)
	ProCapture	44.5 (1130)	54.4 (1382)	53.0 (1346)	–
Height – in (mm)		76.3 (1938)	81.0 (2057)	76.5 (1943) / 77.3 (1963)	85.7 (2177)
Cylinder Diameter – in (mm)		30.0 (762)	33.0 (838)	37.0 (940)	44 (1118)
Cylinder Depth – in (mm)		26.0 (660)	35.0 (889)	36.0 (914)	41 (1041)
Cylinder Volume – cu ft (liters)		10.6 (300)	17.3 (490)	22.4 (634)	36.1 (1022)
Reversing Cylinder		Standard	Standard	Standard	Standard
Door Opening Size – in (mm)		22.7 (576)	26.9 (683)	26.9 (683)	26.9 (683)
Heat Input Power	Standard	73,000 x 2 Btu/hr	120,000 x 2 Btu/hr	150,000 Btu/hr	270,000 Btu/hr
	ProCapture	68,000 x 2 Btu/hr	108,000 x 2 Btu/hr	150,000 Btu/hr	–
Gas Connections* – in (NPT)		0.5	0.75	0.5	1
Air Outlet – in (mm)	Standard	1 x 8 (203) Oval	1 x 10 (254) Oval	8 (203)	10 (254)
	ProCapture	1 x 8 (203) Oval	1 x 10 (254) Oval	10 (254)	–
Motor - HP	Fan	Standard - 2 x 0.5 ProCapture - 2 x 0.5	Standard - 2 x 1.5 ProCapture - 2 x 1.5	Standard - 0.5 ProCapture - 1.5	1.5
	Cylinder	Standard - 2 x 0.5 ProCapture - 2 x 0.5	Standard - 2 x 0.5 ProCapture - 2 x 0.5	Standard - 0.5 ProCapture - 0.5	1.5
Airflow – cfm (liters/sec)	Standard	2 x 400 (189)	2 x 700 (330)	800 (378)	1400 (661)
	ProCapture	2 x 400 (189)	2 x 650 (307)	800 (378)	–
Electrical Specs - amps	(B) 100-120V/50/60/1	Standard - 16 ProCapture - 18	– –	Standard - 12 –	–
	(X) 200-240V/50/60/1/3	Standard - 9 ProCapture - 10	Standard - 14 ProCapture - 18	Standard - 7 ProCapture - 18	– –
	(Q) 200-240V/50/60/3	–	–	ProCapture - 9	7
Shipping Dimensions Approx. – in (mm)	Width	32.5 (826)	35.5 (902)	41.5 (1054)	48 (1219)
	Depth	47.0 (1194)	57.3 (1455)	56.0 (1422)	71.5 (1816)
	Height	79.9 (2029)	85.6 (2174)	81.0 (2057)	90 (2286)
Net Weight – lb (kg)	Standard	580 (263)	735 (333)	720 (327)	1220 (553)
	ProCapture	620 (281)	815 (370)	740 (336)	–
Shipping Weight – lb (kg)	Standard	615 (279)	780 (354)	770 (349)	1290 (585)
	ProCapture	655 (297)	860 (390)	790 (358)	–
Agency Approvals		UL	UL	UL	UL

Laundromat **Stacked & Single Tumble Dryer** Specifications

Models		HTS30	HT055
Control Options		Galaxy™ Touch/600	Galaxy™ Touch/600
Capacity – lb (kg)		30 (13)	55 (25)
Width – in (mm)		31.5 (800)	34.5 (876)
Depth – in (mm)	Standard	41.5 (1054)	53.1 (1349)
	ProCapture	41.5 (1054)	53.1 (1349)
Height – in (mm)		63.9 (1623)	66.3 (1684)
Cylinder Diameter – in (mm)		30.0 (762)	33.0 (838)
Cylinder Depth – in (mm)		26.0 (660)	35.0 (889)
Cylinder Volume – cu ft (liters)		10.6 (300)	17.3 (490)
Reversing Cylinder		Standard	Standard
Door Opening Size – in (mm)		22.7 (577)	26.9 (683)
Heat Input Power	Standard	73,000 Btu/hr	112,000 Btu/hr
	ProCapture	65,000 Btu/hr	110,000 Btu/hr
Gas Connections* – NPT		1/2	1/2
Air Outlet – in (mm)	Standard	6 (152)	8 (203)
	ProCapture	8 (203)	8 (203)
Motor - HP	Fan	Standard - 0.5 ProCapture - 0.5	Standard - 0.5 ProCapture - 1.5
	Cylinder	Standard - 0.5 ProCapture - 0.5	Standard - 0.5 ProCapture - 0.5
Airflow – cfm (liters/sec)	Standard	550 (260)	700 (330)
	ProCapture	450 (212)	650 (307)
Electrical Specs - amps	(B) 100-120V/50/60/1	Standard - 11 ProCapture - 11	Standard - 12 –
	(X) 200-240V/50/60/1/3	Standard - 6 ProCapture - 7	Standard - 7 Standard - 11
Shipping Dimensions Approx. – in (mm)	Width	32.5 (826)	35.5 (902)
	Depth	47.0 (1194)	57.0 (1448)
	Height	68.2 (1732)	70.5 (1791)
Net Weight - lb (kg)	Standard	340 (154)	440 (200)
	ProCapture	365 (166)	495 (225)
Shipping Weight - lb (kg)	Standard	370 (168)	480 (218)
	ProCapture	395 (179)	535 (243)
Agency Approvals		UL	UL

* LP gas available for 75 lb capacity only. Field conversion kits available for other capacities.

Tumble dryer models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the tumble dryer. USA and Canada models are certified by CSA International.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems of Alliance Laundry Systems are registered to ISO 9001.



3 YEARS LIMITED
Galaxy 600



5 YEARS LIMITED
Galaxy Touch

*See Warranty Bond for specifics.